

**C15 ACERT**  
500 ekW/ 625 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor

Rating Type: STANDBY

Fuel Strategy: LOW FUEL CONSUMPTION



**C15 ACERT**  
500 ekW/ 625 kVA  
60 Hz/ 1800 rpm/ 480 V

Image shown may not reflect actual configuration

**Metric**

**English**

**Package Performance**

Genset Power Rating with Fan @ 0.8 Power Factor	500 ekW	
Genset Power Rating	625 kVA	
Aftercooler (Separate Circuit)	N/A	N/A

**Fuel Consumption**

100% Load with Fan	127.2 L/hr	33.6 gal/hr
75% Load with Fan	98.3 L/hr	26.0 gal/hr
50% Load with Fan	69.8 L/hr	18.4 gal/hr
25% Load with Fan	41.7 L/hr	11.0 gal/hr

**Cooling System<sup>1</sup>**

Engine Coolant Capacity	N/A	N/A
-------------------------	-----	-----

**Inlet Air**

Combustion Air Inlet Flow Rate	37.9 m <sup>3</sup> /min	1337.4 cfm
Max. Allowable Combustion Air Inlet Temp	47 ° C	117 ° F

**Exhaust System**

Exhaust Stack Gas Temperature	510.3 ° C	950.6 ° F
Exhaust Gas Flow Rate	102.7 m <sup>3</sup> /min	3627.4 cfm
Exhaust System Backpressure (Maximum Allowable)	10.0 kPa	40.0 in. water

## C15 ACERT

500 ekW/ 625 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor

Rating Type: STANDBY

Fuel Strategy: LOW FUEL CONSUMPTION

**Heat Rejection**

Heat Rejection to Jacket Water	185 kW	10501 Btu/min
Heat Rejection to Exhaust (Total)	477 kW	27109 Btu/min
Heat Rejection to Aftercooler	108 kW	6125 Btu/min
Heat Rejection to Atmosphere from Engine	13 kW	767 Btu/min
Heat Rejection to Atmosphere from Generator	26 kW	1479 Btu/min

**Alternator<sup>2</sup>**

Motor Starting Capability @ 30% Voltage Dip	1239 skVA
Current	752 amps
Frame Size	A2985L4
Excitation	SE
Temperature Rise	163 ° C

**Emissions (Nominal)<sup>3</sup>**

NOx	3377.5 mg/Nm <sup>3</sup>	6.6 g/hp-hr
CO	197.8 mg/Nm <sup>3</sup>	0.4 g/hp-hr
HC	3.0 mg/Nm <sup>3</sup>	0.0 g/hp-hr
PM	9.0 mg/Nm <sup>3</sup>	0.0 g/hp-hr

**DEFINITIONS AND CONDITIONS**

1. For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.
2. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40° C ambient per NEMA MG1-32.
3. Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

**C15 ACERT**  
**500 ekW/ 625 kVA/ 60 Hz/ 1800 rpm/ 480 V/ 0.8 Power Factor**

**Rating Type: STANDBY**

**Fuel Strategy: LOW FUEL CONSUMPTION**

**Applicable Codes and Standards:**

AS1359, CSA C22.2 No100-04, UL142, UL489, UL869, UL2200,  
NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC60034-1, ISO3046, ISO8528,  
NEMA MG1-22, NEMA MG1-33, 2006/95/EC, 2006/42/EC, 2004/108/EC.

Note: Codes may not be available in all model configurations. Please consult your local Cat Dealer representative for availability.

**STANDBY:** Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

**Fuel Rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

[www.Cat-ElectricPower.com](http://www.Cat-ElectricPower.com)

Performance No.: DM8165-03

Feature Code: U.K:C15DEGX, China:C15DEHX

Generator Arrangement: 5027417

Date: 05/12/2016

Source Country: U.K. or China

LEHE1091-00 (05/16)

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.