



The Cat® C27 ACERT™ Industrial Diesel Engine is offered in ratings ranging from 597-783 kW (800-1050 bhp) @ 1800 rpm. These ratings meet U.S. EPA Tier 4 Final emission standards. Industries and applications powered by C27 ACERT engines include: Bore/Drill Rigs, Chippers/Grinders, Construction, Cranes, Dredgers, Forestry, Hydraulic Power Units, Irrigation Equipment, Material Handling, Mobile Earthmoving Equipment, Paving Equipment, Pumps, Shovels/Draglines, Surface Hauling Equipment and Trenchers. Specifications are for configurations with side-mounted turbos. Configurations are also available with rear-mounted turbos for 652 kW (875 bhp) and 708 kW (950 bhp) ratings.

Specifications

Power Rating		
Minimum Power	597 kW	800 BHP
Maximum Power	783 kW	1050 BHP
Rated Speed	1800 rpm	

Emission Standards	
Emissions	U.S. EPA Tier 4 Final

General	
Engine Configuration	V-12, 4-Stroke-Cycle Diesel
Bore	137.2 mm (5.4 in)
Stroke	152.4 mm (6 in)
Displacement	27 L (1649.5 in³)
Aspiration	Twin Turbocharged-Aftercooled (TTA)
Compression Ratio	16.0:1
Combustion System	Direct Injection
Rotation from Flywheel End	Counterclockwise
Cooling System - Capacity	67.9 L (71.7 qt)
Lube System - Refill	68 L (71.9 qt)

Engine Dimensions - Approximate	
Height	1370 mm (53.9 in)
Length	1874 mm (73.8 in)
Weight - Net Dry - Basic Operating Engine Without Optional Attachments	3004 kg (6625 lb)
Width	1600 mm (63 in)

Benefits and Features

Emissions

Meets U.S. EPA Tier 4 Final emission standards.

Reliable, Quiet and Durable Power

World-class manufacturing capability and processes coupled with proven core engine designs assure reliability, quiet operation, and many hours of productive life.

Fuel Efficiency

Fuel consumption optimized to match operating cycles of a wide range of equipment and applications while maintaining low operating costs.

Broad Application Range

Industry leading range of factory configurable ratings and options for agricultural, material handling, construction, mining, aircraft ground support, and other industrial applications.

Package Size

Exceptional power density enables standardization across numerous applications. Multiple installation options minimize total package size. Ideal for equipment with narrow engine compartments.

World-class Product Support Offered Through Global Cat Dealer Network

- Scheduled maintenance, including SOSSM sample
- Customer Support Agreements (CSA)
- Caterpillar Extended Service Coverage (ESC)
- Superior dealer service network
- Extended dealer service network through the Cat Industrial Service Distributor (ISD) program

World-class Product Support Offered Through Global Cat Dealer Network

- Scheduled maintenance, including SOSSM sample
- Customer Support Agreements (CSA)
- Caterpillar Extended Service Coverage (ESC)
- Superior dealer service network
- Extended dealer service network through the Cat Industrial Service Distributor (ISD) program

Standard Equipment

Air Inlet System

- Turbocharged
- Air-to-Air Aftercooled

Control System

- Electronic control system
- Over-foam wiring harness
- Automatic altitude compensation
- Power compensated for fuel temperature
- Configurable software features
- Engine monitoring system SAE J1939 broadcast and control

Cooling System

- Thermostats and housing, vertical outlet

- Jacket water pump, centrifugal
- Water pump, inlet

Exhaust System

- Exhaust manifold, dry
- Optional exhaust outlet

Flywheels and Flywheel Housing

- Choice of SAE No. 0 or SAE No. 1 flywheel housing

Fuel System

- MEUI injection
- Fuel filter, secondary (2 micron)
- Fuel transfer pump
- Electronic fuel priming

Lube System

- Open crankcase ventilation system
- Oil cooler
- Oil filler
- Lube oil filter
- Rear sump oil pan
- Oil dipstick
- Gear driven oil pump

General

- Paint: Caterpillar yellow, with optional colors available at request
- Vibration damper
- Lifting eyes

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S-O-S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.